

Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or design registrations. 除专利、实用新型、外观设计、发明专利、软件著作权、集成电路布图设计专有权、商业秘密和发明创造等权利外，本公司保留对涉及发明、实用新型、外观设计、发明专利、软件著作权、集成电路布图设计专有权、商业秘密和发明创造等权利的所有权利。

FOR-1755 Rev.2.0

2



3







4

5

6


未注公差/General tolerances (mm)

0 ~ 3	>3 ~ 6	>6 ~ 10	>10 ~ 18	>18 ~ 30	>30 ~ 50	>50 ~ 80	>80 ~ 120	>120 ~ 180	>180 ~ 250	>250 ~ 315	>315 ~ 400	>400 ~ 500	>500	 0.1/10
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	 ±2'



8	Shrapnel	Stainless steel	/
7	Spring 1	Stainless steel	/
6	Clamp	Copper	Sn Plated
5	Right-lever	PA66+GF	UL94V-0
4	Left-lever	PA66+GF	UL94V-0
3	Right-housing	PA66	UL94V-0
2	Middle-housing	PA66	UL94V-0
1	Left-housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

UL 标准/UL Standard:	B	C	D
额定电压/电流/Rated Voltage(V)/Current(A)	600/35	600/35	/
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等级/Pollution Degree	III/3	III/2	II/2
额定电压/电流/Rated Voltage(V)/Current(A)	1000/41	1000/41	1000/41
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	8	8	6
线径范围(硬线和软线)/Wire Range(rigid and flexible)(AWG/mm²)	24~ 8/ 0.2~ 10		
间距/Pitch(mm)/线数范围/Poles	7.62/N= 02~ 12P		
剥线长度/Stripping length (mm)	14~ 15		
使用温度范围/Operating temperature(°C)	-40~ + 105		
符合 RoHS 环保要求/Conform to RoHS	Yes		

		MATERIAL:	SURFACE/COLOR:	
APPD: 兰春华		MAT NO./REV:	- / 00	MAT STATUS: 设计放行
CHKD: 龚耀志		NAME		
DRFT: 朱岳鹏		5EDGKDG-7.62-XXP-1Y-00Z (H)		
2024.03.22		DRAWING NO.	TYPE	DRAWING STATUS
2024.03.21		200051164	CUSTOMER DRAWING	work
2024.03.20		SCALE	1:1	SHEET
A4		1/1		

00			朱岳鹏	2024.03.20
REV	ECN	DESCRIPTION	DRFT	DATE

1

2

3

4

5

6